

NEW... NEW... NEW... NEW... NEW... *The ultimate in advanced technology* **TM50 AND TM80**

Product Comparison	TM50
Force OPENING (kg) max.	75
Force CLOSING (kg) max.	48/54*
Specified Force (kg)	50
2,10m OPENING Time (sec.)	12,4
2,10m CLOSING Time (sec.)	16,2

* speeded up mode

Product Comparison	TM80
Force OPENING (kg) max.	100
Force CLOSING (kg) max.	93
Specified Force (kg)	80
2,10m OPENING Time (sec.)	15,6
2,10m CLOSING Time (sec.)	17,5



Technical Information

	TM50	TM80
Force-Setting for Operation	automatic	
Motor	24V DC, low-noise	
Max. Running Speed	18 cm/sec.	14 cm/sec.
Speed in Soft Mode	8 cm/sec.	8 cm/sec.
Lighting	230V AC, max 40W	
Lighting Durance (adjustable)	10 sec. to 10 minutes	
Duty Cycle	50%	
Stand By Power Consumption	2.0 watts	
Power Supply	109-250V AC	
Transformer	230V AC, 24V AC	
Pre-Warning Light	adjustable	
Automatic closing	adjustable	

	TM50	TM80
Net Running Length	2,500mm	
Max. Running Length extended	4,000mm	
Overall Length	3,150mm	
Height Motor Head	80mm	
Length Motor Head	360mm	
Width Motor Head	180mm	
Minimum Space above the door	35mm	
Weight including packaging	18 kg	
Subject to technical alterations		

Supplied with:-

External emergency release

2 x 4 Channel hand transmitters

1 x 1 Channel radio wall remote (no bell wire required)

5 Year Guarantee

For further information and pricing, please contact our sales team:-

Telephone: 01865 400 469 **Email:** info@seip.co.uk **Website:** www.seip.co.uk